

## SAFETY DATASHEET

(Following Regulations (EC) No 1907/2006 & (EC) No 1272/2008)

SDS Number: AR6A

Date of first issue: 01 July 2003

Date of last revision: 01 June 2015

### 1 - Identification of product

#### 1.1 - Identification of Product

**Tradenames:** Albond 65HS, Albond 65HS C, **Albond HS**, Alumor 4370,

The above mentioned products are aluminium resistant castables.

#### 1.2 - Use of Product

These products are monolithic refractories used in lining industrial furnaces, high temperature processing, kilns and metal melting applications

#### 1.3 - Identification of Company

**U.K.** THERMAL CERAMICS LIMITED  
Tebay Road, Bromborough  
Wirral, Merseyside CH62 3PH  
Tel. : +44 (0) 151 334 4030  
Fax : +44 (0) 151 334 1684

#### 1.4 - Emergency information

Tel: + 44 (0) 7931 963 973

Language: English

Opening hours: Only available during office hours

### 2 - Hazard Identification

#### 2.1 - Classification of the substance/ mixture

2.1.1 CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008

Not classified as hazardous according to Classification, Labelling and Packaging regulations (CLP) 1272/2008 EEC

#### 2.2 - Labelling Elements

Not applicable

#### 2.3 - Other hazards which do not result in classification

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure.

These effects are usually temporary.

When mixed with water, an increase in pH will occur. Alkaline mix may be irritating to skin and could cause damage to eyes.

#### CHRONIC RESPIRATORY HEALTH EFFECTS

These products may contain minimal amounts of crystalline silica. Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis).

IARC (International Agency for Research on Cancer) states that there is "sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources to classify crystalline silica as carcinogenic to humans (Group 1)" (Monograph V 68). In making the overall evaluation the Working Group noted however that carcinogenicity in humans was not detected in all industrial circumstances studied.

### 3 - Composition / Information On Ingredients

#### Description

These products have been specifically developed for molten aluminium applications.

#### Composition

COMPONENT	% by weight	CAS No.	REACH Registration Number	Hazard Classification according to CLP
Alumino-silicate	55-85	Not Applicable	Not yet available	Not classified as hazardous
Alumina	< 30	1344-28-1	01-2119817795-27	Not classified as hazardous
Fumed silica	< 10	69012-64-2	01-2119486866-17	Not classified as hazardous
Cement	< 10	65997-16-2	Not yet available	Not classified as hazardous
Non-wetting additives	< 5	Not Applicable	Not yet available	Not classified as hazardous
Commissioning additives	< 0,5	Not Applicable	Not yet available	Not classified as hazardous

#### composition additional information

None of the components are radioactive under the terms of European Directive Euratom 96/29.

### 4 - First-Aid measures

#### 4.1 - Description of First Aid Measures

##### Skin

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

##### Eyes

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical attention if irritation persists.

##### Nose and Throat

If these become irritated move to a dust free area, drink water and blow nose. Seek medical attention if irritation persists.

#### first aid additional information

If symptoms persist, seek medical advice.

#### 4.2 - Most important symptoms and effects, both acute and delayed

No symptoms or effects expected either acute or delayed

#### 4.3 - Indication of any immediate medical attention and special treatment needed

No special treatment required, if exposure occurs wash exposed areas to avoid irritation.

### 5 - Fire-fighting measures

#### 5.1 - Extinguishing media

Use extinguishing agent suitable for surrounding combustible materials.

#### 5.2 - Special hazards arising from the substance or mixture

Non-combustible products,

#### 5.3 - advice for firefighters

Packaging and surrounding materials may be combustible.

## 6 - Accidental Release Measures

### 6.1 - Personal precautions, protective equipment and emergency procedures

Provide the workers with appropriate protective equipment until the situation is restored to normal (see section 8).

### 6.2 - Environmental precautions

Prevent further dust dispersion for example by damping the materials.  
Do not flush spillage to drain and prevent from entering natural watercourses.  
Check for local regulations, which may apply

### 6.3 - Methods and materials for containment and clean up

Pick up large pieces and use a vacuum cleaner.  
If brushes are used, ensure that the area is wetted down first.  
Do not use compressed air for clean up.  
Do not allow to become windblown.

### 6.4 - Reference to other sections

For further information, please refer to sections 7 and 8

## 7 - Handling and storage

### 7.1 - Precautions for safe handling

Handling can be a source of dust emission and therefore the processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., using dust exhaust system).  
Regular good housekeeping will minimise secondary dust dispersal.

### 7.2 - Conditions for safe storage

Store in original packaging in a dry area.  
Avoid damaging the packaging.  
Material supplied in multi-ply paper sacks or big bags.

### 7.3 - Specific end use

Please refer to your local Morgan Thermal Ceramics' supplier.

## 8 - Risk Management Measures / Exposures Controls / Personal Protection

### 8.1 - Control parameters

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of exposure limits for respirable dust (in November 2014) are given below:

COUNTRY	Total Dust (mg/m3)	Resp Dust (mg/m3)	Quartz (mg/m3)	Cristobalite (mg/m3)	Source
Denmark	10	5	0.10	0.05	Direktoratet for Arbejdstilsynet
Finland	No limit	No limit	0.20	0.10	National Board of Labour Protection
France	1	5	0.10	0.05	Ministère du Travail
Germany*	10	3	No limit	No limit	Bundesministerium für Arbeit
Italy	10	3	0.025	0.025	Associazione Italiana Degli Igienisti Industriali
Netherlands	10	5	0.075	0.075	Ministerie van Sociale Zaken en Werkgelegenheid
Norway	10	5	0.10	0.05	Direktoratet for Arbejdstilsynet
Poland	No limit	No limit	0.30	0.30	
Romania	10	10	0.10	0.05	Government Decision n° 1093/2006 regarding carcinogenic agents
Spain	10	3	0.10	0.05	ITC/2585/2007
Sweden	10	5	0.10	0.05	National Board of Occupational Safety and Health
UK	10	4	0.10	0.10	EH40/2005

\*Germany does not have a limit for crystalline silica, exposure must be minimised as far as possible.

#### Information on monitoring procedures

United Kingdom

MDHS 14/4 - "General methods for sampling and gravimetric analysis of respirable, thoracic and inhalable aerosols"

MDHS 101 - "Crystalline silica in respirable airborne dusts"

NIOSH

NIOSH 0500 "Particulates not otherwise regulated, total"

NIOSH 0600 "Particulates not otherwise regulated, respirable"

NIOSH 7500 " Silica, Crystalline, by XRD (filter redeposition)"

## **8.2 - Exposure controls**

### **8.2.1 APPROPRIATE ENGINEERING CONTROLS**

Review your applications in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and materials handling equipment.

Keep the workplace clean. Use a vacuum cleaner. Avoid brushing and compressed air.

If necessary, consult an industrial hygienist to design workplace controls and practices.

The use of products specially tailored to your application(s) will help to control dust. Some products can be delivered ready for use to avoid further cutting or machining. Some could be pre-treated or packaged to minimise or avoid dust release during handling.

Consult your supplier for further details

### **8.2.2 - Personal Protective Equipment**

Skin protection:

Use of gloves and work clothes is recommended.

Soiled clothes should be cleaned before being taken off (e.g. use vacuum cleaning, not compressed air).

Eye protection:

As necessary wear goggles or safety glasses with side shields.

Respiratory protection:

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short-term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or local Thermal Ceramics' supplier.

## **INFORMATION AND TRAINING OF WORKERS**

Workers should be trained on good working practices and informed on applicable local regulations

### **8.2.3 - Environmental Exposure Controls**

Refer to local, national or European applicable environmental standards for release to air water and soil.

For waste, refer to section13

## 9 - Physical and chemical properties

<b>Information on basic physical and chemical properties</b>	Not applicable
<b>Appearance</b>	Mix of light grey aggregates and fine powders
<b>Odour</b>	None
<b>Odour threshold</b>	Not Applicable
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	> 1450°C
<b>Initial boiling point and boiling point range</b>	Not applicable
<b>Flash point</b>	Not applicable
<b>Evaporation rate</b>	Not Applicable
<b>Flammability (solid, gas)</b>	Not applicable
<b>Upper/lower flammability or explosive limits</b>	Not applicable
<b>Vapour pressure</b>	Not applicable
<b>Vapour density</b>	Not Applicable
<b>Relative density</b>	>2 T/m <sup>3</sup>
<b>Solubility(ies)</b>	Not applicable
<b>Partition co-efficient: n-octanol/water</b>	Not applicable
<b>Auto-ignition temperature</b>	Not applicable
<b>Decomposition temperature</b>	Not Applicable
<b>Viscosity</b>	Not Applicable
<b>Explosive properties</b>	Not applicable
<b>Oxidising properties</b>	Not applicable
<b>Other safety information</b>	Not applicable

## 10 - Stability and Reactivity

### 10.1 - Reactivity

The material is stable and non reactive.

### 10.2 - Chemical Stability

The product is inorganic, stable and inert

### 10.3 - Possibility of Hazardous Reactions

None

### 10.4 - Conditions to Avoid

Careful heat up of the product is essential to avoid rapid loss of the chemical combined water during heat up (see section 16).

### 10.5 - Incompatible Materials

None

### 10.6 - Hazardous decomposition products

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

## 11 - Toxicological information

### Toxicokinetics, metabolism and distribution

#### 11.1.1 BASIC TOXICOKINETICS

As manufactured, these products may contain a minimal amount of crystalline silica. Please refer to composition table in § 3 and trade names in the title.

Exposure is predominantly by inhalation or ingestion, available toxicological information is as follows:

#### 11.1.2 HUMAN TOXICOLOGICAL DATA

##### EPIDEMIOLOGY FOR CRYSTALLINE SILICA

Prolonged/repeated inhalation of respirable crystalline silica dust may cause delayed lung injury (silicosis).

In evaluating crystalline silica as a cancer risk, the International Agency for Research on Cancer (IARC) reviewed several studies from different industries and concluded that crystalline silica from occupational sources inhaled in the form of quartz or cristobalite is carcinogenic to humans (Group 1) [IARC Monograph vol.68; June 1997].

However, in reaching its conclusion, IARC stated that the carcinogenicity in humans could not be found in all industries reviewed and that carcinogenicity might be dependent on inherent characteristics of crystalline silica or on external factors affecting biological activity (e.g., cigarette smoking) or distribution of its polymorphs

### 11.1 - Information on toxicological effects

Experimental studies for crystalline silica

Animals exposed to very high concentrations of crystalline silica, artificially or by inhalation, have reported fibrosis and tumours (IARC Monographs 42 and 68).

Inhalation and intratracheal installation of crystalline silica in rats caused lung cancer. However, studies in other species such as mice and hamsters caused no lung cancer. Crystalline silica also caused fibrosis in rats and hamsters in several inhalation and intratracheal installation studies.

#### ACUTE TOXICITY

Lethal dose 50 % (LD50) / lethal concentration 50% (LC50): N.A.

#### Irritant properties

## 12 - Ecological information

### 12.1 - Toxicity

These products are inert materials that remain stable overtime.  
No adverse effects of this material on the environment are anticipated.

### 12.2 - Persistence and degradability

Not established

### 12.3 - Bioaccumulative potential

Not established

### 12.4 - Mobility in soil

No information available

### 12.5 - Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent and very bioaccumulative (vPvB).

### 12.6 - Other adverse effects

No additional information available

## 13 - Disposal Considerations

### 13.1 - Waste treatment methods

Waste from these materials may be generally disposed off at a landfill, which has been licensed for this purpose. Please refer to the European list (Decision N° 2000/532/CE as modified) to identify your appropriate waste number, and insure national and/or regional regulations are complied with.

Unless wetted, such a waste is normally dusty and so should be properly sealed in containers for disposal. At some authorised disposal sites, dusty waste may be treated differently in order to ensure they are dealt with promptly to avoid them being windblown. Check for any national and/or regional regulations, which may apply.

## 14 - Transport information

### Transport

#### 14.1. UN number

Not Applicable

#### 14.2. UN proper shipping name

Not Applicable

#### 14.3. Transport hazard class(es)

Not Applicable

#### 14.4. Packing group

Not Applicable

#### 14.5. Environmental hazards

Not Applicable

#### 14.6. Special precautions for user

Not Applicable

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable



## 15 - Regulatory information

### 15.1 - Safety health and environment regulations/legislation specific for the substances or mixtures

EU regulations:

- Council Directive 67/548/EEC "on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances as modified and adapted to the technical progress" (OJEC L 196 of 16 August 1967, p.1 and its modifications and adaptations to technical progress).
- Council Directive 1999/45/EC of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations (OJ L 200 of 30.7.1999)
- Regulation (EC) No 1907/2006 dated 18th December 2006 on Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 dated 20th January 2009 on classification, labelling and packaging of substances and mixtures (OJ L 353)
- Commission Directive 97/69/EC of 5 December 1997 adapting to technical progress for the 23rd time Council Directive 67/548/EEC (OJEC of 13 December 1997, L 343).
- Commission regulation (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures.
- The 1st Adaptation to Technical Progress (ATP) to Regulation (EC) No 1272/2008 enters into force on 25 September 2009. It transfers the 30th and 31st ATPs of Directive 67/548/EEC to the Regulation (EC) No 1272/2008.

#### PROTECTION OF WORKERS

Shall be in accordance with several European Directives as amended and their implementations by the Member States:

- a) Council Directive 89/391/EEC dated 12 June 1989 "on the introduction of measures to encourage improvements in the safety and health of workers at work" (OJEC (Official Journal of the European Community) L 183 of 29 June 1989, p.1).
- b) Council Directive 98/24/EC dated 7 April 1998 "on the protection of workers from the risks related to chemical agents at work" (OJEC L 131 of 5 May 1998, p.11).

#### OTHER POSSIBLE REGULATIONS

Member States are in charge of implementing European Directives into their own national regulation within a period of time normally given in the Directive. Member States may impose more stringent requirements. Please always refer to any national regulation.

### 15.2 - Chemical Safety Assessment

Chemical Safety Reports have been requested from suppliers, as soon as this information is available it will be shared with downstream users.

## 16 - Other Information

### Useful references

(the directives which are cited must be considered in their amended version)

- Council Directive 89/391/EEC dated 12 June 1989 "on the introduction of measures to encourage improvements in the safety and health of workers at work" (OJEC L 183 of 29 June 1989, p.1).
- Regulation (EC) No 1907/2006 dated 18th December 2006 on registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 dated 20th January 2009 on classification, labelling and packaging of substances and mixtures (OJ L 353)
- Commission Directive 97/69/EC of 5 December 1997 adapting to technical progress for the 23rd time Council Directive 67/548/EEC (OJEC of 13 December 1997, L 343).
- Council Directive 98/24/EC of 7 April 1998 "on the protection of the health and safety of workers from the risks related to chemical agents at work" (OJEC L 131 of 5 May 1998, p11).

### Precautionary measures

#### ADDITIONAL INFORMATION AND PRECAUTIONS TO BE CONSIDERED UPON REMOVAL OF AFTER SERVICE MATERIAL

Continuous use of these products at temperatures above 900°C may, as with many other refractories, lead to the formation of cristobalite (a type of crystalline silica).

Please refer to sections 2, 11 and to national regulation on crystalline silica.

Crystalline silica may be present in concentration over passing 1% due to fluctuation of raw materials composition.

High concentrations of dusts may be generated when after-service products are mechanically disturbed during operations such as wrecking. Therefore Morgan Thermal Ceramics recommends:

- a) control measures are taken to reduce dust emissions;
- b) all personnel directly involved wear an appropriate respirator to minimise exposure; and
- c) Compliance with local regulatory limits.

### RECOMMENDED HEATING PROCEDURE

Cure for 24 hours, air dry for 24 hours minimum and raise to 110-130°C and hold for 6 hours (<300mm lining) or 24 hours (300-500mm lining) or until steam ceases. Raise to 550/600°C at 25°C per hour and hold for 6-8 hours. Raise to working temperature at 50°C per hour (<300 mm lining) or 25°C (300-500 mm lining). For linings thicker than 500 mm or installations greater than 30 tons, contact Thermal Ceramics. This information is only a guide. Please refer, for each product, to the defined commissioning schedules provided by Morgan Thermal Ceramics

### CARE Program

#### Uses advised against

#### Website

For more information connect to:

The Morgan Thermal Ceramics' website: (<http://www.morganthermalceramics.com/>)

Or ECFIA's website: (<http://www.ecfia.eu>)

### Revision Summary

Amendments to sections 1, 2, 3, 4, 5, 6, 8, 9, 12, 14, 15 and 16 to comply with CLP regulations

### Technical data sheets

For more information on individual products please see the relevant technical data sheet available from <http://www.morganthermalceramics.com/downloads/datasheets>

### Other Information

#### NOTICE:

The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However safe as provided by law, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorisation given or implied to practice any patented invention without a licence. In addition, no responsibility can be assumed by the vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product (however, this shall not act to restrict the vendor's potential liability for negligence or under statute).